

increased, the gains from spatial prediction increase rapidly. However, the overall detection probability remains low. As the number of prediction points is increased (corresponding to the right panel of Figure 2) the spatial prediction approach starts to perform very well, over tripling the detection probability for coverage holes compared to the measurements only-approach. We also see that the false alarm probability remains stable.

Figure 3 shows the results for the urban scenario where measurements and predictions are carried out in the annulus with $d_{\min} = 265$ m and $d_{\max} = 335$ m. This corresponds to drive tests carried out specifically at the cell edge, where coverage holes are most likely to occur. We see that especially for larger ratio of number of prediction points to measurement points the spatial prediction scheme yields approximately 90% detection probability for coverage holes, with significantly improved performance compared to measurements only approach.

Figure 4 shows the results for the rural scenario focusing on the annulus with $d_{\min} = 400$ m and $d_{\max} = 800$ m. The overall detection probabilities are lower than for the urban case (due to the same number of measurement points being used to cover much larger area compared to the urban case), but the gains from the spatial prediction approach are still very clear.

5. CONCLUSIONS

In this paper we studied the use of a spatial Bayesian prediction framework for improving coverage estimates for cellular networks based on measurements. Our results indicate that the use of techniques from modern spatial statistics can significantly increase the accuracy of coverage predictions from drive test data. We are currently extending our evaluation work with additional scenarios, including measurements from live cellular systems.

Acknowledgments

We thank EU for providing partial funding of this work through the FARAMIR project. JR and PM also thank RWTH Aachen University and DFG for partial financial support through the UMIC research centre.

6. REFERENCES

- [1] 3GPP. TS 37.320 v10.0.0, “Radio measurement collection for Minimization of Drive Tests (MDT);Overall description; Stage 2”.
- [2] A. Alaya-Feki, S. Ben Jemaa, B. Sayrac, P. Houze, and E. Moulines. Informed spectrum usage in cognitive radio networks: Interference cartography. In *Proceedings of IEEE PIMRC 2008*, pages 1–5. IEEE, 2008.
- [3] T. Cai, J. van de Beek, B. Sayrac, S. Grimoud, J. Nasreddine, J. Riihijärvi, and P. Mähönen. Design of layered radio environment maps for ran optimization in heterogeneous LTE systems. In *Proceedings of IEEE PIMRC 2011*, pages 172–176. IEEE, 2011.
- [4] M. L. Eaton. *Multivariate Statistics: a Vector Space Approach*. John Wiley and Sons, 1983.
- [5] M. Gudmundson. Correlation model for shadow fading in mobile radio systems. *Electronics Letters*, 27:2145–2146, 1991.
- [6] H.-S. Jo and J.-G. Yook. Path loss characteristics for IMT-advanced systems in residential and street environments. *IEEE Antennas and Wireless Propagation Letters*, pages 867–871, 2010.
- [7] H. Omre. Bayesian kriging—merging observations and qualified guesses in kriging. *Mathematical Geology*, 19(1):25–39, 1987.
- [8] H. Raiffa and R. Schlaifer. *Applied Statistical Decision Theory*. Wiley, 2000.
- [9] J. Riihijärvi, P. Mähönen, M. Petrova, and V. Kolar. Enhancing cognitive radios with spatial statistics: From radio environment maps to topology engine. In *Proceedings of CROWNCOM’09*, pages 1–6, 2009.
- [10] J. Riihijärvi, P. Mähönen, M. Wellens, and M. Gordziel. Characterization and modelling of spectrum for dynamic spectrum access with spatial statistics and random fields. In *Proceedings of IEEE PIMRC 2008*, pages 1–6. IEEE, 2008.
- [11] G. Senarath, W. Tong, P. Zhu, H. Zhang, D. Steer, D. Yu, M. Naden, and D. Kitchener. Multi-hop relay system evaluation methodology (channel model and performance metric). *IEEE C802. 16j-06/013r3*, 2007.
- [12] Y. Zhao, L. Morales, J. Gaeddert, K. Bae, J. Um, and J. Reed. Applying radio environment maps to cognitive wireless regional area networks. In *Proceedings of IEEE DySPAN 2007*, pages 115–118. IEEE, 2007.